

PPF Maintenance Guidelines:

- 1. Wait 48 Hours After Installation: Please refrain from washing your vehicle for at least 48 hours after the PPF installation to allow it to properly set.
- 2. Stain Removal: Promptly remove any insect or other stains using XPEL Film Cleaner (PPF CLEANER). For stubborn stains, you can use 99% isopropyl alcohol. Be cautious not to allow these chemicals to come into contact with your vehicle's paint.
- 3. Seal with XPEL Ceramic Boost: To maintain a high gloss and protect the film, apply XPEL Ceramic Boost at least once every 6 months.
- 4. Self-Healing for Light Scratches: Light scratches on the film will self-heal in approximately 20-30 minutes at room temperature. If you are in colder conditions or wish to expedite the healing process, pour warm water (at around 120°F) over the affected area.
- 5. Avoid High-Pressure Water Sources: Exercise caution when using pressure washers or high-pressure water sources near the edges of the film. High pressure can cause the film to lift or become damaged.
- Contaminant Removal with Detailing Clay: Detailing clay can be safely used to remove contaminants that may accumulate on the film over time.
 Regularly inspect and clean the film to maintain its appearance and protective qualities.

By adhering to these care and maintenance instructions, you can help ensure that your Paint Protection Film continues to provide the desired protection and appearance for your vehicle.

Paint Protection Film Terms & Conditions of Sale

Paint protection film is an 8mil film designed to protect your vehicle's paint from paint chips, scratches and swirl marks. It is applied to the exterior of your vehicle paint. It is warrantied for 10 years from yellowing, staining, cracking, blistering and delamination. There is no warranty if film or protected panel get damage in an accident or from debris.

1. Drying Time

 Your new paint protection film will take 3-4 weeks to fully cure depending on weather conditions. Do not wash your vehicle for 5 days.
Vehicles should be returned for inspection within 2-4 weeks.

2. Condition of Vehicle for Paint Protection Film Installation

 Vehicle cannot have any paint protection coatings on it such as ceramic coatings. These can affect the effectiveness of the adhesion and may cause lifting, bubbles and other issues. Client is aware that the design of the PPF is for OEM factory paint. The client waives and releases Tint City from any warranty or damage claims where a product has been applied to a non-OEM paint surface.

3. Paint Quality

 Paint may lift on repainted panel/OEM paint if improperly prepped and painted. By authorizing Tint City to proceed with the install, the client herby acknowledges the risk, waives any claims against Tint City and agrees that Tint City will not be liable in the event that damage does occur during the installation process.

4. Paint Chips

PPF is to prevent your vehicle from future paint chip damage. PPF installation over paint chips will look like contamination after the install due to the unevenness of the paint surface. We do not recommend touch up on small paint chips due to the aesthetics of the install thereafter.

5. Installation

 All PPF kits are computer cut using cutting software. Pre-cut kits involve stopping short of edges, edges around badges, washers, and other parts. The customer understands that PPF is a sacrificial layer of your car, not a completely invisible or matte layer.

6.Expose Edges and Seams

 Although we strive to wrap all edges, some cannot be wrapped. Debris build up over time on exposed edges/seams will be more visible on white/light coloured vehicles. Partial installs will have more noticeable debris due to exposed edges. There is no warranty or reapplication of film due to debris build up.

7. Headlights

 Headlights are not recommended for PPF installation due to HID feature and exterior coating. By authorizing Tint City to proceed with headlight film installation, the customer hereby acknowledges the risk, waives any claims against Tint City, and agrees that Tint City will not be liable.

8. Film, Badge, & Decal Removal

 Film, badge, and decal removal may cause the paint, glass, and defroster to be damaged. By authorizing Tint City to proceed with removal, the client hereby acknowledges the risk, waives any claims against Tint City and agrees that Tint City will not be liable in the event that damage does occur during the removal process.

9. Imperfections

 Though we strive for perfection in our installations, due to the nature of the product, some degree of dust contamination and or minor imperfections are present in every PPF application, also pre-existing flaws, scratches, and rock chips on the paint are often much more noticeable after the PPF is installed. Paint Protective Film will have minor imperfections like orange peel. Used and older vehicle will have more imperfections due to its age.

Customer Name	
Signature	
Date -	